

Cisco/санс цисководства – Urbanculture

[обратно к статье «Cisco»](#)

Цены · сеанс цисководства

Типичный сеанс цисководства

```

Router>enable
Router#show interfaces summary

*: interface is up
IHQ: pkts in input hold queue      IQD: pkts dropped from input queue
OHQ: pkts in output hold queue     OQD: pkts dropped from output queue
RXBS: rx rate (bits/sec)          RXPS: rx rate (pkts/sec)
TXBS: tx rate (bits/sec)          TXPS: tx rate (pkts/sec)
TRTL: throttle count

Interface           IHQ   IQD   OHQ   OQD   RXBS  RXPS  TXBS  TXPS  TRTL
-----
FastEthernet0/0        0     0     0     0     0     0     0     0     0
NOTE:No separate counters are maintained for subinterfaces
      Hence Details of subinterface are not shown

Router#configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#hostname r1
r1(config)#int
r1(config)#interface fa0/0
r1(config-if)#ip addr 192.0.2.1 255.255.255.0
r1(config-if)#no sh
00:06:09: %LINK-3-UPDOWN: Interface FastEthernet0/0, changed state to up

r1(config-if)#do sh run | section interface
interface FastEthernet0/0
 ip address 192.0.2.1 255.255.255.0
 duplex half
r1(config-if)#

```